


HATCHED AREA INDICATES LEAVE OUT CONCRETE. INSTALL #4 X 1'-6" SMOOTH DOWELS AT 12" OC AT THE ENTIRE PERIMETER. ALLOW THE VAPOR BARRIER TO EXTEND 6" MIN PAST THE EDGE OF THE PERIMETER SLAB. FINE GRADE TO 4" BELOW FINISHED FLOOR AND INSTALL 4" OPEN GRADED AGGREGATE. SEE DETAIL 102 SHEET A1-12

100A  
BUILDING A  
(12,209 SF)



SAMPLE ONLY

COPYRIGHT BY  
CREATIVE CONCEPTS AND DESIGN, INC.

- PRELIMINARY NOT FOR CONSTRUCTION
- ISSUED FOR BIDDING
- ISSUED FOR PERMIT
- ISSUED FOR CONSTRUCTION

Drawing Status  
Owner  
Project  
Sheet Title

FLOOR PLAN  
BUILDING A

Drawn By  
Issue Date:  
Drawing File Name  
1412\_A1-1\_Floor Plan.dwg  
Revisions  
No. \_\_\_\_\_ Date \_\_\_\_\_  
No. \_\_\_\_\_ Date \_\_\_\_\_  
No. \_\_\_\_\_ Date \_\_\_\_\_  
No. \_\_\_\_\_ Date \_\_\_\_\_

Project Number  
17-13  
Building

Sheet \_\_\_\_\_ Of \_\_\_\_\_  
A1-1.1